
Small Package Low Capacitance TVS

Compliance Standard

- ◆ IEC 61000-4-2 (ESD)
8KV - Contact Discharge
15KV - Air Discharge
- ◆ IEC 61000-4-4 (EFT) 40A (5/50ns)
- ◆ IEC 61000-4-5 (Surge) 2.0 (8/20us)

Applications


- ◆ Data Interface Protection
- ◆ Embedded System
- ◆ Handheld Device
- ◆ Computer

Features

- ◆ 100W Peak Pulse Power
- ◆ Low Clamping Voltage
- ◆ Low Leakage Current
- ◆ Single Line, Uni-Directional

Mechanical Characteristics

- ◆ DFN-1610 Package (0603)
- ◆ Weight 3 Milligram (Approximate)
- ◆ Flammability Rating UL94V-0
- ◆ Lead Free Plating
- ◆ Reel Size 7"
- ◆ 3000 PCS Per Reel

Package

DFN-1610

Pin Configuration

DEVICE CHARACTERISTICS

Maximum Rating			
Parameter	Symbol	Value	Unit
Peak Pulse Power	P _{PP}	100	Watt
Lead Soldering Temperature	T _L	260 (10s)	°C
Operating Temperature Range	T _J	-55~150	°C
Storage Temperature Range	T _{STG}	-55~150	°C

Electrical Characteristics (@25 °C)							
Part Number	Marking	V _{RWM} (Volt)	V _B (Volt)	V _C (Volt)	I _{PP} (A)	I _R (uA)	C _J (pF)
NLULC24TN	SAF	24.0	26.7	50.0	2.0	1.0	0.6




Figure1. Clamping waveform of positive 8KV ESD contact





Figure2. Clamping waveform of negative 8KV ESD contact

DEVICE OUTLINE

Outline Dimension				
Symbol	Millimeters		Inches	
	Min	Max	Min	Max
A	1.55	1.65	0.061	0.065
B	0.95	1.05	0.037	0.041
C	0.40	0.50	0.015	0.020
H	0.02	0.05	0.000	0.002
L1	0.75	0.85	0.029	0.033
L2	0.35	0.45	0.013	0.018
L4	1.10TYP		1.10TYP	



LAYOUT PAD DIMENSION

<i>Layout PAD Dimension</i>				
Symbol	Millimeters		Inches	
	Min	Max	Min	Max
A	1.80	1.90	0.070	0.075
B	0.95	1.05	0.037	0.041
C	1.20	1.30	0.047	0.051



<i>Revision History</i>	<i>Description</i>
v2.0	Re-organize datasheet layout